

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY'S DOCKET NUMBER

134.1012

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

To Be Assigned **09/807227**INTERNATIONAL APPLICATION NO.
PCT/EP00/07821INTERNATIONAL FILING DATE
August 11, 2000PRIORITY DATE CLAIMED
August 11, 1999

TITLE OF INVENTION

METHOD AND DEVICE FOR PERFORMING ONLINE ABERROMETRIE IN RETRACTIVE EYE
CORRECTION INDICES

APPLICANT(S) FOR DO/EO/US

Manfred DICK, et al.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☐ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail
20. ☒ Other items or information:

- Letter re: Priority

APPLICATION NO. (IF KNOWN, SEE 37 CFR
 1.52(b)) **09/807227**
 To Be Assigned

 INTERNATIONAL APPLICATION NO.
PCT/EP00/07821

 ATTORNEY'S DOCKET NUMBER
134.1012

21. The following fees are submitted:

CALCULATIONS PTO USE ONLY
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO **\$1,000.00**
☒ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO **\$860.00**
☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO **\$710.00**
☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) **\$690.00**
☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) **\$100.00**

ENTER APPROPRIATE BASIC FEE AMOUNT =
\$860.00

 Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

\$0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	
Total claims	16 - 20 =	0	x \$18.00	\$0.00
Independent claims	3 - 3 =	0	x \$80.00	\$0.00
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>				\$0.00

TOTAL OF ABOVE CALCULATIONS =
\$860.00

 Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐
\$0.00
SUBTOTAL =
\$860.00

 Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

\$0.00
TOTAL NATIONAL FEE =
\$860.00

 Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☐
\$0.00
TOTAL FEES ENCLOSED =
\$860.00

Amount to be:	\$
refunded	
charged	\$

- ☒ A check in the amount of **\$860.00** to cover the above fees is enclosed.
☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees.
 A duplicate copy of this sheet is enclosed.
☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **50-0552** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

 William C. Gehris, Reg. No. 38,156
 DAVIDSON, DAVIDSON & KAPPEL, LLC
 485 Seventh Avenue, 14th Floor
 New York, New York 10018

23280

PATENT TRADEMARK OFFICE

SIGNATURE

William C. Gehris

NAME

38,156

REGISTRATION NUMBER

April 6, 2001

DATE

134.1012

UNITED STATES PATENT AND TRADEMARK OFFICE

Re: Application of: DICK, Manfred et al.
Serial No.: To Be Assigned
International
Application No.: PCT/EP00/07821
Filed: Herewith
For: METHOD AND DEVICE FOR PERFORMING ONLINE
ABERROMETRIE IN REFRACTIVE EYE
CORRECTION INDICES

Asst. Commissioner for Patents
Washington, D.C. 20231

April 9, 2001

PRELIMINARY AMENDMENT

Sir:

Applicants request amendment of the above-identified application prior to a first examination on the merits, as follows:

IN THE SPECIFICATION:

Before paragraph [0001], insert the heading --BACKGROUND OF THE INVENTION--.

Before paragraph [0006], insert the heading --SUMMARY OF THE INVENTION--.

Delete paragraph [0007].

Replace paragraph [0032] as follows:

[0032] Moreover, the objective is achieved by an ideal optical system which is manufactured according to a method according to the present invention and/or using a device according to the present invention, the optical system including elements made of materials which are suitable for implantation and/or for adhesion and/or for ablation, in particular plastic or glass. By selecting these materials of the lens system according to the present invention, compatibility in using these elements

is guaranteed. Such materials are, for example, PMMA, acrylic, silicone, or a combination of these materials.

Before paragraph [0035], insert the heading --BRIEF DESCRIPTION OF THE DRAWINGS--.

Before paragraph [0039], insert the heading --DETAILED DESCRIPTION--.

IN THE CLAIMS:

Please amend claims 1-14 and 16 as follows:

1. (Amended) A method for correcting visual defects of an eye comprising:
 - a coherent light source,
 - a beam modification device for shaping and deflecting a beam of the coherent light source,
 - and
 - a wavefront analyzer device for analyzing a wavefront of an optical path in the eye.
2. (Amended) The device as recited in Claim 1, further comprising a topography analyzer unit for analyzing the surface of the eye.
3. (Amended) The device as recited in claim 1, further comprising a control unit for at least one of processing signals of the wavefront analyzer unit; processing signals of the topography analyzer unit; for controlling the coherent light source; and for controlling the beam modification device.
4. (Amended) The device as recited in claim 1, wherein the beam modification device is designed in such a manner that at least one of an intraocular lens; an eye lens; the cornea of the eye; a contact lens; an implantable contact lens (ICL); and a spectacle lens are processable via the beam.
5. (Amended) The device as recited in claim 1, wherein the coherent light source is a laser.

6. (Amended) The device as recited in claim 3, wherein the control unit is designed in such a manner that the analysis of the optical path in the eye and/or the analysis of the surface of the eye can be carried out virtually simultaneously with the processing of an optical element via the beam of the coherent light source.

7. (Amended) A method for correcting visual defects of an eye comprising:
determining an optical path of the eye via a wavefront analysis; and
calculating an ideal optical system which would result in a correction of the visual defects of the eye.

8. (Amended) The method as recited in claim 7, further comprising analyzing the topography of the eye.

9. (Amended) The method as recited in claim 7, wherein the ideal optical system is provided as a function of data obtained from at least one of the wavefront analysis and the topography analysis.

10. (Amended) The method as recited in claim 7, further comprising calculating shot positions for manufacturing the ideal optical system as a function of data obtained from at least one of the wavefront analysis and the topography analysis.

11. (Amended) The method as recited in claim 7 further comprising reshaping the old optical system of the eye into the calculated ideal optical system.

12. (Amended) The method as recited in claim 7, wherein the optical system includes at least one of the eye lens; an intraocular lens; the cornea of the eye; a contact lens; an ICL; and at least one spectacle lens.

13. (Amended) An ideal optical system manufactured according to the method of claim 7 wherein the optical system includes elements made of materials which are suitable for at least one of implantation; adhesion; and ablation.

14. (Amended) The ideal optical system as recited in claim 13 wherein the optical system includes elements having refractive and/or diffractive structures.

16. (Amended) The method as recited in claim 7 further including completely correcting a visual defect of an eye.

Please add new claims 17 to 20:

17. The device as recited in claim 5 wherein the laser is a spot scanning excimer laser.

18. The system as recited in claim 13 wherein the materials are plastic or glass.

19. An ideal optical system manufactured using one of the devices according to claim 1 wherein the optical system includes elements made of materials which are suitable for at least one of implantation; adhesion; and ablation.

20. The system as recited in claim 19 wherein the materials are plastic or glass.

REMARKS


Consideration of this application, as amended, is respectfully requested.

By virtue of this amendment, claims 1-14 and 16 have been amended in order to conform the claims of the international application, of which this application is a national stage application, to proper U.S. Patent and Trademark Office practice. Support for all new claims is found in the specification as originally filed. No new matter has been added, and no new claims have been added.

Applicants believe that no fees are due as a result of this amendment. In the event of a fee discrepancy, please charge our Deposit Account No. 50-0552.

Respectfully submitted,

DAVIDSON, DAVIDSON & KAPPEL, LLC

By: 

William C. Gehris
Reg. No. 38,156


Davidson, Davidson & Kappel, LLC
485 Seventh Avenue - 14th Floor
New York, New York 10018
(212) 736-1940

"Express Mail" mailing label no. EL 743183971 US

Date of deposit: April 9, 2001

I hereby certify that this correspondence and/or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above in an envelope addressed to "Commissioner of Patents and Trademarks, Washington, DC 20231"

DAVIDSON, DAVIDSON & KAPPEL, LLC

BY: 

VERSION OF SPECIFICATION AMENDMENTS
WITH MARKINGS TO SHOW CHANGES

[0032] Moreover, the objective is achieved by an ideal optical system which is manufactured according to a method according to the present invention and/or using a [devices] device according to the present invention, the optical system including elements made of materials which are suitable for implantation and/or for adhesion and/or for ablation, in particular plastic or glass. By selecting these materials of the lens system according to the present invention, compatibility in using these elements is guaranteed. Such materials are, for example, PMMA, acrylic, silicone, or a combination of these materials.

VERSION OF CLAIMS AMENDMENTS
WITH MARKINGS TO SHOW CHANGES MADE

1. A method for correcting[, in particular refractive] visual defects of an eye [(1),] comprising:
a coherent light source [(4)],
a beam modification device [(5)] for shaping and deflecting a beam of the coherent light source [(4)], and
[wherein provision is made for] a wavefront analyzer device [(2)] for analyzing a wavefront of [the] an optical path in the eye [(1)].
2. The device as recited in Claim 1, further comprising
[wherein, in addition, provision is made for] a topography analyzer unit [(2')] for analyzing the surface of the eye [(1)].
3. The device as recited in [one of the preceding claims which are related to a device] claim 1,
[wherein, moreover, provision is made for] further comprising a control unit [(3)] for at least one of processing signals of the wavefront analyzer unit [(2)] and/or
for]; processing signals of the topography analyzer unit [(2') and/or] ;

for controlling the coherent light source [(4) and/or]; and
for controlling the beam modification device [(5)].

4. The device as recited in [one of the preceding claims which are related to a device] claim 1,
wherein the beam modification device [(5)] is designed in such a manner that at least one of an
intraocular lens [and/or]; an eye lens [and/or]; the cornea of the eye [(1) and/or]; a contact lens
[and/or]; an implantable contact lens (ICL) [and/or]; and a spectacle lens are processable via the
beam.

5. The device as recited in [one of the preceding claims which are related to a device,] claim 1,
wherein the coherent light source [(4)] is a laser[, in particular a spot scanning excimer laser
system].

6. The device as recited in [one of the Claims 3 through 5] claim 3,
wherein the control unit [(3)] is designed in such a manner that the analysis of the optical path in
the eye [(1)] and/or the analysis of the surface of the eye [(1)] can be carried out virtually
simultaneously with the processing of an optical element via the beam of the coherent light source
[(4)].

7. A method for correcting[, in particular refractive] visual defects of an eye [(1), in
particular using a device as recited in the preceding claims,] comprising:
determining an [wherein the] optical path of the eye [is determined] via a wavefront analysis; and
calculating an ideal optical system [is calculated] which would result in a correction of the visual
defects of the eye [(1)].

8. The method as recited in Claim 7, further comprising analyzing[wherein] the topography of the
eye [(1) is analyzed as well].

9. The method as recited in [one of the preceding method claims] claim 7, wherein the ideal optical system is provided [on the basis of the] as a function of data obtained from at least one of the wavefront analysis [and/or from] and the topography analysis.

10. The method as recited in [one of the preceding method claims] claim 7, further comprising calculating [wherein, moreover,] shot positions for manufacturing the ideal optical system [are calculated with the assistance of the] as a function of data obtained from at least one of the wavefront analysis [and/or from] and the topography analysis.

11. The method as recited in [one of the preceding method claims,] claim 7 further comprising reshaping [wherein] the old optical system of the eye [(1) is reshaped] into the calculated ideal optical system.

12. The method as recited in [one of the preceding method claims] claim 7, wherein the optical system includes at least one of the eye lens ; [and/or] an intraocular lens; [and/or] the cornea of the eye; [and/or] a contact lens; [and/or] an ICL; and [and/or] at least one spectacle lens.

13. An ideal optical system manufactured according to [one of the preceding method claims and/or using one of the devices as recited in the preceding claims which are related to devices,] the method of claim 7 wherein the optical system includes elements made of materials which are suitable for at least one of implantation [and/or]; [for] adhesion [and/or for]; and ablation[, in particular plastic or glass].

14. The ideal optical system as recited in [one of the preceding claims which are related to an optical system,] claim 13 wherein the optical system includes elements having refractive and/or diffractive structures.

16. [The use of a] The method as recited in [one of the preceding method claims and/or of a device] claim 7 [as recited in one of the preceding claims which are related to devices, for] further including completely correcting a visual defect of an eye.

16. [The use of a] The method as recited in [one of the preceding method claims and/or of a device] claim 7 [as recited in one of the preceding claims which are related to devices, for] further including completely correcting a visual defect of an eye.

3/PRTS

09/807227

JC02 Rec'd PCT/PTO 09 APR 2001

134.1012

METHOD AND DEVICE FOR PERFORMING ONLINE ABERROMETRY IN
REFRACTIVE EYE CORRECTION

[0001] The present invention relates to a method and a device for correcting visual defects of the human eye.

[0002] In ophthalmology, it is known to shape the cornea by ablation of tissue in the case of amblyopia. In this context, the data on the aberration in the optical path of the eye is obtained by questioning the patient about his/her subjective impression of vision on the basis of corrections via standardized corrective lenses in front of the eye of the patient. Besides, methods exist for measuring the outer contour of the eye with the assistance of stripe- or ring-projection systems as are manufactured, for example, by the Orbtek, Tomey, or Technomed companies.

[0003] German Patent Application DE 197 05 119 A1 describes a method for improving a Shack-Hartmann sensor which can be used in the field of astronomy to measure wavefronts for surveying stars.

[0004] In German Patent 197 27 573 C1, a device and a method for shaping surfaces, in particular of lenses, by laser ablation of the surfaces is specified in a valuable contribution to the technological development.

[0005] It is felt to be a disadvantage of the related art that the correction of the lenses takes place only on the basis of suboptimum data on the causes of the visual defects such as irregularities of the cornea surface or aberration in the optical path. Consequently, only corrections according to the standard lens formulas of geometric optics are carried out.

[0006] Therefore, the object of the present invention is to provide a method and a device which permit complete correction of all refractive visual defects, including the aberrations of the optical path in the defective eye.

[0007] This objective is achieved by the device and the method according to the independent claims. Advantageous embodiments of the present invention are specified in the subclaims.

[0008] In particular, the objective is achieved by a device for correcting visual defects of an eye, including a coherent light source, a beam modification device for shaping and deflecting a beam of the coherent light source, provision being made for a wavefront analyzer device for analyzing a wavefront of the optical path in the eye. This device enables the data obtained from the analysis of the intraocular aberration to be taken into account in the correction of an existing optical system of an eye to be corrected. In this manner, the correction of the optical system of the eye is achievable with added precision.

[0009] The considered eye can be, in particular, a human eye but it is also conceivable to correct eyes of other living beings. Visual defects are, in particular, refractive visual defects such as myopia or hyperopia, irregularities of the cornea surface, or aberrations in the optical path.

[0010] Provided as coherent light source is preferably a laser, especially preferably a refractive laser, particularly preferably a spot scanning excimer laser. Conceivable is, moreover, a spot scanner using laser light in other ranges of the spectrum, such as a frequency-quintupled YAG laser, an IR laser of around $3\mu\text{m}$ such as an Erbium:YAG laser emitting at $2.94\mu\text{m}$ or a femtosecond laser (fs Laser).

[0011] The beam modification device is preferably composed of a device for shaping a beam and of a device for deflecting and aligning the beam. Preferably used as the device for shaping the beam are lens systems, diffractive structures, and refractive elements. Preferably used as the device for deflecting and aligning the beam are scanner arrangements, prisms, and mirrors.

[0012] Preferably usable as wavefront analyzer device is a Shack-Hartmann sensor, which is a sensor that is based on a method for analyzing wavefronts and is used, in particular, in astronomy (see above). Using this wavefront analyzer device, it is possible to measure the whole wavefront emerging from the eye and, in this manner, to acquire data on the visual defects, including the intraocular aberration of the optical path also in the eye.

[0013] In a further exemplary embodiment of the present invention, provision is made for a device in which a topography analyzer unit for analyzing the surface of the eye is provided, as well. This analysis provides the data on the curvature and contour possessed by the eye surface, i.e., in particular by the cornea. In this manner, the complete data on the refractive visual defects of the eye is available to the system. Both the possibly not optimum surface contour of the eye, i.e., of the cornea, and the intraocular aberration can now be analyzed and are available to the system in the correction of the optical system of the eye. In this manner, it is possible to completely correct the visual defects of the eye and even to achieve a vision which exceeds that of the normal human eye.

[0014] In a further exemplary embodiment of the present invention, provision is made for a device in which, moreover,

a control unit for processing signals of the wavefront analyzer unit and/or for processing signals of the topography analyzer unit and/or for controlling the coherent light source and/or for controlling the beam modification device is provided. These control units permit evaluation of the data ascertained by the analyzer units. It is possible for the signals of the wavefront analyzer unit and the signals of the topography analyzer unit to be separately processed and evaluated in the control unit, or to process both data sets in one step. The control unit is preferably composed of several individual control units.

[0015] This data is preferably used for providing an ideal optical system. The parameters required for beam modification is determined from this data. These parameters can preferably be used in a further step for controlling the coherent light source, for example, to predetermine amplitude, pulse duration, and energy of the beam. Moreover, these parameters are also preferably used for controlling the beam modification device; here, to predetermine the target spot and the geometry of the beam in the target via the deflection of the beam.

[0016] Because of this, it is possible in a preferred exemplary embodiment to calculate, in particular, the shot positions for manufacturing the individual elements.

[0017] In a further preferred exemplary embodiment of the present invention, provision is made for a device in which the beam modification device is designed in such a manner that an intraocular lens and/or an eye lens and/or the cornea of the eye and/or a contact lens and/or an implantable contact lens (ICL) and/or a spectacle lens are processable via the beam. The beam, which is preferably controlled by the control unit, now enables an element or workpiece of the lens system to be processed in such a manner that the visual defects or

aberration are completely corrected. Such an element is preferably an intraocular lens (IOL) which is prefabricated prior to a corresponding operation. This is particularly preferably an ICL (implantable contact lens) which is placed onto the lens. Based on the entire available data on the visual defects, including the aberration of the eye, this IOL or ICL can be shaped in such a manner that it corrects all existing visual defects. It is also conceivable for the correction to be carried out on the eye lens itself with the assistance of the beam which is preferably controlled by the control unit.

[0018] Moreover, it is conceivable to carry out a correction by processing the cornea. It is also preferred to manufacture contact lenses which, in a patient-specific manner, correct all individual defects going beyond the refractive eye defect, such as aberrations, unsymmetrical cylinders, and irregularities of the cornea. Besides, it is also possible to manufacture individual spectacle lenses. Besides excimer spot processing, methods of the optical industry, such as the single point diamond turning method, can also be used for this purpose. In this manner, all elements of the affected optical system can be used for correcting the eye defects.

[0019] It is also possible to use a combination of the individual (partly) corrected elements. This is an advantage, in particular if the theoretically possible correction via one element would result in excessive stressing of this element, and if such stressing appears not to be advisable, in particular from the medical point of view.

[0020] In a further preferred exemplary embodiment of the device according to the present invention, the control unit is designed in such a manner that the analysis of the optical path in the eye and/or the analysis of the surface of the eye

can be carried out virtually simultaneously with the processing of an optical element via the beam of the coherent light source. Due to this modification of the control unit, an "online" test of the optical path in the eye such as it is currently modified via the operation and/or of the surface of this eye at the current point of time can be carried out during the processing of the optical element, i.e., for example during the processing of the cornea via the surgical laser beam, and be taken into account in the further operation or processing. During a laser treatment of the cornea for correcting refractive visual defects of the eye, it is thus possible for the prevailing refractive value of the overall visual apparatus of the eye to be continuously measured and for the sequence of treatment to be exactly adjusted online to the target value of the refraction of the eye in the case that disturbing influences on the treatment are present. This optimized treatment is made possible by this combination of the optical systems of a surgical laser for the ablation of cornea tissue or lens material and of an aberrometer for the analysis of wavefronts or of the surface of the eye. Particularly advantageous in this context is the complete ascertainment of the refractive values (spherocylindrical aberrations and aberrations of higher order) of the whole optical apparatus of the eye which, in the final analysis, are representative of the quality of the attained surgical intervention. By performing the ascertainment completely online and without interrupting the sequence of treatment, provision is made for an optimized device in terms of the time sequence and the attainable precision.

[0021] Particularly preferably, it is also possible for the analysis of the optical path or of the surface of the eye to be carried out in alternation with the processing of the optical element, thus ascertaining portion-by-portion the progression of the treatment or of the operation of the

optical system, in particular of the cornea. It is also conceivable for the scanning and analysis of the optical path or of the surface of the eye to be time-interleaved with the processing via the surgical laser beam. This permits continuous or virtually continuous measurement combined with real device integration (e.g., every second) and continuous recalculation of the laser control.

[0022] Moreover, the objective is achieved by a method according to the present invention for correcting visual defects of an eye, the optical path of the eye being determined via a wavefront analysis, and an ideal lens system being calculated which would result in a correction of the visual defects of the eye. This method is particularly preferably employed using a device according to the present invention. In this method, the intraocular aberration of the optical path is available for calculating the correction of the optical system for conversion into an ideal optical system.

[0023] In a further method according to the present invention, it is particularly preferred to analyze the topography of the eye as well. In this method, consequently, additional data on the defective vision of the eye is available, in particular on aberrations, unsymmetrical cylinders, and irregularities of the cornea.

[0024] In another preferred method, the ideal optical system is provided on the basis of the data obtained from the wavefront analysis and/or from the topography analysis. For this, it is particular preferred to provide only one element from this optical system. In this manner, the correcting element or the correcting elements is/are manufactured in a further step on the basis of the complete data of the defective vision. This procedure thus leads to the complete

correction of the defective vision.

[0025] In a further preferred method, shot positions for manufacturing the ideal optical system are calculated using the data obtained from the wavefront analysis and/or from the topography analysis. In this manner, it is advantageously possible to use the laser spot excimer method for manufacturing the individual elements of the optical systems. The shot positions are optimized depending on the materials to be used and considering the time needed for manufacture.

[0026] In another method of the present invention, the old optical system of the eye is reshaped into the calculated ideal optical system. To this end, either elements of the old optical system are processed directly or correspondingly corrected elements are manufactured and inserted or old elements are replaced with new elements. This method allows the old (defective) optical system of the eye to be converted into a (new) ideal optical system. It is especially preferred to manufacture a new lens or an ICL according to the spot scanning principle using an excimer laser.

[0027] It is particularly preferred in the method according to the present invention to process a contact lens which is already located on the eye of the patient. During measurement, the patient preferably wears already a contact lens correcting standard visual defects or, in the case of emmetropia, only a therapeutic contact lens which especially preferably features good adhesion and constant image characteristics without decentering. Now, the ablation is carried out on the standardized contact lens, thus non-invasively attaining a riskless correction of the higher aberration of the eye. This allows, in particular, higher aberrations to be corrected without risk to the patient and with high treatment safety to enable the optical apparatus of the eye to utilize the

resolving power of the retina and to be provided with a super-vision which is superior to that of the normally-seeing eye. Regardless of the characteristics of their own eyes in terms of transmittance values or drying of the tear film, patients can now acquire a preferred super-vision and gain experience therewith in everyday life. The old vision characteristic is restored by removing the contact lens.

[0028] For this purpose, it is also preferred to use a therapeutic contact lens without refractive effect. In this connection, all image defects are corrected on this contact lens with the assistance of the laser.

[0029] It is particularly preferred to use contact lenses made of PMMA or plastic lenses which, compared to the human cornea, especially preferably feature a small material ablation for the used laser, for example, a 193 nm ArF excimer laser. Particularly preferred are also all soft contact lenses which exhibit nearly the same ablation characteristics as the cornea because of their high water content. Thus, it is possible to determine the exact ablation rates for any standardized-manufacture contact lens material prior to the treatment and, because of this, to carry out a desired refractive correction on the eye in a reproducible manner.

[0030] The correction possibility simulated in this manner can serve in a preparatory manner for a later real cornea operation, or such a lens having a customized correction can be used for a predetermined time. In particular in the case of hard contact lenses, longer-term use is also possible. In this context, a corresponding marking for the axial orientation is applied which is paid attention to during insertion.

[0031] The optical system preferably includes, as elements, the eye lens and/or an intraocular lens and/or the cornea of

the eye and/or a contact lens and/or an ICL and/or at least one spectacle lens. Via refractive surgery, it is possible, for example, for the cornea of the eye to be reshaped so as to correct the existing defective vision (for example, the surface of the cornea via photorefractive keratectomy, PRK, or by ablation of inner tissue layers of the cornea using laser assisted in situ keratomileusis, LASIK). These elements not only feature rotationally geometric corrections but individual structures for correcting the defective vision of the patients. In this manner, it is possible to manufacture intraocular lenses or contact lenses, in particular ICLs which, once they are brought into the lens system, not only roughly correct the defective vision of the eye as in known methods heretofore but which additionally correct all irregularities, unsymmetries, and beam distortions, as well. In this manner, it is possible to attain a vision which exceeds that of the normal human eye. Besides, this method makes it possible to manufacture spectacle lenses which likewise correct all irregularities, unsymmetries, and beam distortions of the defective eye or of the old optical system, as well.

[0032] Moreover, the objective is achieved by an ideal optical system which is manufactured according to a method according to the present invention and/or using a devices according to the present invention, the optical system including elements made of materials which are suitable for implantation and/or for adhesion and/or for ablation, in particular plastic or glass. By selecting these materials of the lens system according to the present invention, compatibility in using these elements is guaranteed. Such materials are, for example, PMMA, acrylic, silicone, or a combination of these materials.

[0033] In a further exemplary embodiment of the present invention, provision is made for an ideal optical system including elements which contain refractive and/or diffractive structures. In known methods heretofore, refractive and/or diffractive structures are only used in beam shaping. A minilens system guides and shapes the entering beam to attain a special beam distribution in the target plane. The use of such refractive and/or diffractive structures on individual elements of an optical system allows visual defects to be selectively corrected in an exceptionally ideal manner. Using these structures, it is thus possible to correct individual, non-steady aberrations but also to give the optical systems characteristics which a normal human eye does not possess.

[0034] The objective of the present invention is achieved, moreover, by an element of an (ideal) lens system having refractive and/diffractive structures. Such elements can include intraocular lenses, modified cornea, contact lenses, ICLs, or spectacle lenses.

[0035] In the following, exemplary embodiments of the present invention and advantageous refinements will be explained in greater detail on the basis of drawings. In this context,

[0036] Fig. 1 shows a block diagram for an exemplary embodiment of a device according to the present invention for correcting an aberration in the optical path of an eye on a lens 6;

[0037] Fig. 2 shows a block diagram for an exemplary embodiment of a device according to the present invention for correcting an aberration in the optical path of an eye to which a lens 6 is applied;

[0038] Fig. 3 shows a block diagram for an exemplary embodiment of a device according to the

present invention for correcting an aberration in the optical path of an eye on without contact lens.

[0039] **Figure 1** depicts a block diagram for an exemplary embodiment of a device according to the present invention for correcting visual defects of an eye on a lens. A wavefront analyzer unit 2 and a topography analyzer unit 2' are connected to a control unit 3. Control unit 3 is connected to a laser 4 and to a beam modification device 5 via a bus. A lens 6 is depicted downstream of beam modification device 5. An eye 1 is shown upstream of wavefront analyzer unit 2 and topography analyzer unit 2'.

[0040] In the operating state, the beams of wavefront analyzer unit 2 and topography analyzer unit 2' scan eye 1 and transmit the obtained signals to control unit 3. The beams which are used here are preferably beams of a coherent light source, especially preferably beams of an IR diode or of a green laser. In control unit 3, the signals are processed and the ideal optical system for this eye 1 is calculated. In the depicted case, an ideal lens 6 is calculated here as element of the optical system. In control unit 3, in particular, all shot positions needed for laser 4 to manufacture ideal lens 6 are calculated on the basis of the data obtained from the signals, taking into account the laser-relevant data. Subsequently, control unit 3 triggers laser 4, determining energy and pulse rate of beam 7. Beam 7 is guided through beam modification device 5. In beam modification device 5, beam 7 is shaped and deflected via scanners and lens systems according to the calculated shot positions via the input of control unit 3, so that customer-specific lens 6 is manufactured by ablation of material on the raw lens via controlled surgical laser beam 7. Preferably, control unit 3 can also be designed in several partial control units which

can be connected to individual components of the device.

[0041] **Figure 2** depicts a block diagram for a further exemplary embodiment of a device according to the present invention for correcting an aberration in the optical path of an eye to which a lens is applied. In principle, the configuration corresponds to that of Figure 1 with the difference that a contact lens 6 is directly applied to eye 1 and that the ablation is carried out there in situ. To this end, surgical laser beam 7 is directed, preferably via further optical elements such as mirrors (not shown), to lens 6 which rests directly on eye 1. The ablation of the lens material is now carried out in situ on the eye so that the optical path in the system of eye 1 and lens 6 as well as the surface of this system, i.e., here preferably of lens 6, can now be analyzed, preferably online, via analyzer device 2 or 2' concurrently with the ablation, and the treatment via beam 7 can be directly checked and assessed. Ideal lens 6 manufactured in this manner now conveys to the interested person an impression of the complete optical system and of the surgical conditions without having undergone an irreversible operation.

[0042] **Figure 3** depicts a block diagram for an exemplary embodiment of a further device according to the present invention for correcting the aberration in the optical path of an eye without contact lens. Here, preferably simultaneously with the analysis of eye 1 via analyzer device 2, 2', the progression of the operation can be monitored online via the surgical beam 7, and recalculations can be carried out via control unit 3 during the operation so that eye 1 can be treated iteratively via laser beam 7 which reacts and is used in each case as a function of the prevailing conditions. Besides, the progression of the operation can also be

monitored visually, for example, via a microscope (not shown).

[0043] It is particularly preferred to project a point onto the retina of eye 1 with the assistance of a light source of analyzer device 2, 2' (light source not separately shown). In this context, a nearly parallel external optical path is used, making use of the focusing effect of the optical apparatus of the eye to be able to generate an as small as possible point. In accordance with the used wavelength and the irradiation time, the intensities are so small that no damage can occur on the retina but sufficient reflected intensity exists.

[0044] While passing through the aberrative optical system of the eye, the reflective wave detects all image defects. The correspondingly deformed wavefront reaches wavefront analyzer device 2 or topography analyzer device 2' from where the aberration data is preferably fed to a computer via a corresponding electronics or control unit 3. With the assistance of the computer software, a current ablation profile is in each case calculated from the aberration data, the ablation profile triggering excimer laser 4 including the spot scanning system, implementing a target-controlled treatment via beam modification device 5.

[0045] Such a measurement can also be carried out sporadically, for example, during 80 percent of the treatment time. Analyzer device 2 or 2' can be arranged on a separate stand so that laser and measuring instrument swing in alternately or, preferably, the measuring instrument is integrated in the laser and measures when the laser bombardment is interrupted. It is particularly preferred for a recalculation of the remaining treatment to be carried out on request of the operator. This measurement can particularly preferably be carried out also continuously or virtually continuously in the case of device integration and continuous

recalculation of the laser control.

[0046] In this manner, a new and advantageous method and a device for completely correcting visual defects of the human eye have been specified. Combinations of measuring and processing methods have been specified which, when used according to the present invention, enable the human eye to be completely corrected. In doing so, measuring methods are used which can precisely measure the surface of the cornea and which also record the aberrations arising in the further optical path up to the retina. The computer-aided evaluation of these measuring results, in conjunction with the calculation of ideally corrected eye lenses (for example, after cataract operations) or of ideally correcting cornea surfaces, makes it possible to manufacture a patient-specific lens and/or to shape the cornea in an ideally correcting manner, preferably using a spot scanning excimer laser system in a topography-aided manner.

[0047] In particular, the correction can be effected via the modification of an element of the optical system. Thus, for improving the vision of a patient having a cataract and a defective vision, it is sufficient to completely correct the intraocular lens. In such a case, it is no longer necessary to carry out a refractive operation in addition to the cataract operation.

LIST OF REFERENCE SYMBOLS

- 1 Eye
- 2 Wavefront analyzer device
- 2' Topography analyzer unit
- 3 Control unit
- 4 Coherent light source
- 5 Beam modification device
- 6 Optical element/lens

What is claimed is:

1. A method for correcting, in particular refractive visual defects of an eye (1), comprising
a coherent light source (4),
a beam modification device (5) for shaping and deflecting a beam of the coherent light source (4),
wherein provision is made for a wavefront analyzer device (2) for analyzing a wavefront of the optical path in the eye (1).
2. The device as recited in Claim 1,
wherein, in addition, provision is made for a topography analyzer unit (2') for analyzing the surface of the eye (1).
3. The device as recited in one of the preceding claims which are related to a device,
wherein, moreover, provision is made for a control unit (3) for processing signals of the wavefront analyzer unit (2) and/or
for processing signals of the topography analyzer unit (2') and/or
for controlling the coherent light source (4) and/or
for controlling the beam modification device (5).
4. The device as recited in one of the preceding claims which are related to a device,
wherein the beam modification device (5) is designed in such a manner that an intraocular lens and/or an eye lens and/or the cornea of the eye (1) and/or a contact lens and/or an implantable contact lens (ICL) and/or a spectacle lens are processable via the beam.
5. The device as recited in one of the preceding claims which are related to a device,

wherein the coherent light source (4) is a laser, in particular a spot scanning excimer laser system.

6. The device as recited in one of the Claims 3 through 5, wherein the control unit (3) is designed in such a manner that the analysis of the optical path in the eye (1) and/or the analysis of the surface of the eye (1) can be carried out virtually simultaneously with the processing of an optical element via the beam of the coherent light source (4).

7. A method for correcting, in particular refractive visual defects of an eye (1), in particular using a device as recited in the preceding claims, wherein the optical path of the eye is determined via a wavefront analysis; and an ideal optical system is calculated which would result in a correction of the visual defects of the eye (1).

8. The method as recited in Claim 7, wherein the topography of the eye (1) is analyzed as well.

9. The method as recited in one of the preceding method claims, wherein the ideal optical system is provided on the basis of the data obtained from the wavefront analysis and/or from the topography analysis.

10. The method as recited in one of the preceding method claims, wherein, moreover, shot positions for manufacturing the ideal optical system are calculated with the assistance of the data obtained from the wavefront analysis and/or from the topography analysis.

11. The method as recited in one of the preceding method claims,

wherein the old optical system of the eye (1) is reshaped into the calculated ideal optical system.

12. The method as recited in one of the preceding method claims,

wherein the optical system includes the eye lens and/or an intraocular lens and/or the cornea of the eye and/or a contact lens and/or an ICL and/or at least one spectacle lens.

13. An ideal optical system manufactured according to one of the preceding method claims and/or using one of the devices as recited in the preceding claims which are related to devices, wherein the optical system includes elements made of materials which are suitable for implantation and/or for adhesion and/or for ablation, in particular plastic or glass.

14. The ideal optical system as recited in one of the preceding claims which are related to an optical system, wherein the optical system includes elements having refractive and/or diffractive structures.

15. An element for use in an optical system, wherein the element has refractive and/or diffractive structures.

16. The use of a method as recited in one of the preceding method claims and/or of a device as recited in one of the preceding claim which are related to devices, for completely correcting a visual defect of an eye.

Abstract

This invention relates to a method and a device for the complete correction of sight defects in the human eye. Combinations of measuring, and processing methods are described which when applied as disclosed in the invention, make it possible to fully correct sight defects in the human eye. Measuring methods are used which can precisely scan the surface of the cornea and also register other imaging defects in the light path up to the retina. Computer-aided of said measuring results determined when combined with calculation of ideally corrected ocular lenses (for example after cataract operations) or ideally corrected surfaces of the cornea opens up the possibility of manufacturing a patient-specific lens and/or achieving ideal correction of the cornea using preferably a topography-supported spot-scanning-excimer laser system.




Fig. 1




Fig. 2




Fig. 3

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that.

My residence, post office address and citizenship are as stated below next to my name

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **METHOD AND DEVICE FOR PERFORMING ONLINE ABERROMETRIE IN RETRACTIVE EYE CORRECTION INDICES**, the specification of which (check one)

☒ is attached hereto
was filed on _____ as Application Serial No. _____
and was amended on _____ (if applicable).
☒ I hereby authorize and request our attorney, Davidson, Davidson & Kappel, LLC, of 485 Seventh Avenue, 14th Floor, New York, New York 10018 to insert here in parentheses (Application number 09/807, 227, filed 4/9/01) the filing date and application number of said application when known.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information which is known to me to be material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign and/or provisional application(s) for patent or inventor's certificate listed below and have also identified below any foreign and/or provisional application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

PRIOR APPLICATION(S)			Priority claimed	
<u>DE 199 38 203.4</u>	<u>Germany</u>	<u>11 August 1999</u>	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)		
_____	_____	_____	<input type="checkbox"/> Yes	<input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)		

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial Number)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)
_____ (Application Serial Number)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)

And I hereby appoint Clifford M. Davidson, Registration No. 32,728, Leslye B. Davidson, Registration No. 38,854, Cary S. Kappel, Registration No. 36,561, William C. Gehrs, Registration No. 38,156, Morey B. Wildes, Registration No. 36,968, Robert J. Paradiso, Registration No. 41,240, Erik R. Swanson, Registration No. 40,833, Scott L. Appelbaum, Registration No. 41,587, Cynthia R. Moore, Registration No. 46,086, David Knasiak, Registration No. 45,991, Salvatore J. Maiorino, Registration No. 42,830, my attorneys, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith; correspondence address: DAVIDSON, DAVIDSON & KAPPEL, LLC, 485 Seventh Avenue, 14th Floor, New York, New York 10018; Telephone: (212) 736-1940; Fax: (212) 736-2427.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Manfred DICK
Inventor's signature Manfred Dick
Date 05/09/2001
Residence Gefell, Germany
Citizenship German
Post Office Address: D-07926 Gefell, Germany

Full name of joint inventor, if any Eckhard SCHROEDER
Inventor, if any Eckhard Schroeder
Second Inventor's signature Eckhard Schroeder
Date 05/09/2001
Residence Eckental, Germany
Citizenship German
Post Office Address: D-90542 Eckental, Germany

Full name of joint inventor, if any Joachim FIEDLER
Inventor, if any Joachim Fiedler
Third Inventor's signature Joachim Fiedler
Date 05/09/2001
Residence Crailsheim, Germany
Citizenship German
Post Office Address: Mittlerer Weg 84
D-74564 Crailsheim, Germany

Full name of joint inventor, if any _____
Inventor, if any _____
Fourth Inventor's signature _____
Date _____
Residence _____
Citizenship _____
Post Office Address: _____